



# Product data sheet

Issue date: 19/02/20



# **Polyester Wet System flat mop**

Polyester flat mop, looped end internal and cut end external, polyester support



| Technical information |       |                    |                 |   |     |      |                |
|-----------------------|-------|--------------------|-----------------|---|-----|------|----------------|
| code                  | notes | cm (comm. sizes)   | cm (real sizes) | С | pcs | kg   | m <sup>3</sup> |
| 00000547              |       | J 40 J 14          | J 44 J 14,5     |   | 25  | 4,43 | 0,028          |
| 00000542              |       | <b>.</b> ↓ 50 ⊥ 16 | J 52,5 J 17     |   | 25  | 5,3  | 0,036          |

#### **SYSTEM**

Flat mop system with flaps, to be used with roll, jaw or flat wringer ldeal for greasy and residual dirt thanks to the polyester absorption power of greasy dirt and the yarn structure

#### Advantages

- Time-saving: thanks to the large cleaning surface and the possibility of reaching corners and cleaning under furniture
- Ergonomic: lightweight, it reduces operator's strain

#### Material

Yarn: 70% polyester, 30% cotton - Support: polyester

### Washing conditions

#### Guidelines for proper fibre maintenance

Follow the washing instructions (temperatures and dosage) on the detergent packaging Perform a pre-wash in cold water to remove any residual product used during cleaning operations Do not use fabric softener

It is recommended to use the convenient laundry nets in washing machine in order to preserve the fibres Recommended use of normal textile detergent

Do not use detergents with Ph> 11





19/02/20



Washing temperature max 90° C, recommended 60°



Bleaching only with oxygen, do not use chlorine or bleach



Do not tumble dry or in a dryer

## Related products



**Wet System Light frame** 



Telescopic handle



**Action Pro Dry** 



**Dry wringer** 

## **Product options**



**Wet System Tris flat mop**