

TASKI[®] Jontec Technique

Floor sealer

Description

Semi permanent floor sealer for the basic treatment of most types of porous hard floors. Specific polymers used in the product fill the pores, facilitate adhesion and help reduce the consumption of further coats of floor emulsion. By ensuring the proper adhesion, subsequent floor emulsions will show greater durability.

Key properties

- Facilitates adhesion
- Semi permanent layer
- Fills the pores
- Reduces the consumption of the floor emulsion on top

Benefits

- Ideal to use on most problematic material, floors and surfaces
- Conventional floor emulsions can be selectively removed without affecting the sealer
- Prepares the floor to ease the application of floor emulsions on porous or damaged floors
- Allows savings on application of floor emulsion
- Suitable for traditional applications with a flat mop, mop and bucket or standard polish applicators

Use instructions

- 1. Treat only stripped, thoroughly rinsed and completely dry floors.
- 2. Sparingly pour onto the floor and evenly spread with an appropriate polish applicator.
- 3. Sparingly pour product onto floor in lanes of 1-1.5m with lanes overlapping when still wet.
- 4. Allow to dry the floor completely (20-40 minutes). Apply a second coat on very porous floors.
- 5. Allow to dry completely and then apply further coats of your choice of Diversey standard floor emulsion until the desired appearance is reached.

Dosage:

Ready to use, no dilution required.





° A.I.S.



тазкі[®] Jontec Technique

Technical data Appearance: Milky, white liquid pH value (neat): ≈ 8.5 pH value (in use): ≈ 8.5 Relative density (20°C): 1.03 g/cm³ *The above data is typical of normal production and should not be taken as a specification.*

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists. Do not store or use at temperatures below 5°C.

Product compatibility

Treat only stripped, thoroughly rinsed and completely dry floors. Do not use on wooden floors. Apply only to completely cured (dried out) cement and armoured concrete floors.

Available pack sizes

TASKI Jontec Technique is available in 2x5L.