

Method card





BUZIL-WERK Wagner GmbH & Co. KG

INDUMASTER® STRONG IR 45

Application area: Floor



pH 13.5

Dilution	100 - 500 ml / 10 l water	  	
Suitable for	Industrial applications and workshop areas; Fire-damage restorations; Cleaning machine & high pressure cleaning machine	Not suitable for	Acrylic glass; Painted / colored surfaces; Natural and artificial stone floors; Aluminum
Application	Alkali resistant floors and surfaces; Concrete floors; Resin floors; Safety tiles		
 Trouble Shooting Before initial use: Test material compatibility!	Issue / Failure / Requirement <ul style="list-style-type: none"> ▪ Leaves streaks; film on surface in daily routine cleaning ▪ Low; weak cleaning effect ▪ No cleaning effect ▪ Damage on surface (discoloration, material swelling, etc.) ▪ Grey; mat appearance of surface due to hard water 	Solving Issue <ul style="list-style-type: none"> ▪ Adjust product dilution; rinse with clean water ▪ Select alkaline intensive cleaner i.e. Indumaster® Offensive IR 47 ▪ Select problem solver i.e. Indumaster® Forte IR 42 ▪ Check material's chemical & water resistance ▪ Clean periodically with O Tens Azid G 501 	

Method card

BUZIL-WERK Wagner GmbH & Co. KG

ALTERNATIVE PRODUCT | INDUMASTER® STRONG IR 45

Application area:
Floor



pH 13.5

Alternative Product	Differentiation	Application
Indumaster® Offensive IR 47	Dissolves stubbornest of encrustations	Intensive cleaning / degreasing
Indumaster® Fast IR 14	Fast separating acc. ÖNORM B 5105	Intensive cleaning / degreasing / fast drying
Indumaster® Forte IR 42	Solvent based industrial cleaner	Removal of rubber (fork lift marks)