



FLOOR CLEANER

Basic cleaner

CORRIDOR® POWER STRIPPER S 708

High-performance universal basic cleaner



Fields of application

- For water-resistant, alkaline-sensitive elastic floor coverings, such as linoleum, elastomer coverings, and PVC
- For removal of stubborn coatings and care films that are multi-coated, metal ion cross-linked and free of inorganic salt

Product advantages/properties

- For universal use
- Outstanding dissolving action on encrustations and compressed care films
- Fast-acting and residue-free dissolving of coatings
- Low dosage, very economical
- High material compatibility
- Foam-inhibited
- Very high dispersive capacity for optimum surface action
- Time saving and powerful thanks to special solubility promoters

Technical data

pH-Value	9,5
Product colour	colourless to yellowish
Container*	5 l canister

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.





FLOOR CLEANER

Basic cleaner

CORRIDOR® POWER STRIPPER S 708

High-performance universal basic cleaner

Application and dosage



2,5 l : 10 l water

Depending on age, type and number of coatings.



Spread cleaning solution evenly over floor. Allow short contact time. Carry out basic cleaning using a rotar buffer or floor scrubbing machine and suitable pad or brush. Vacuum up dirt solution. Rinse floor with clear water. Vacuum up rinse water.

Note

Always use cold water.

Not suitable for asphalt or bitumen floorings.

Do not mix with other cleaners.

Test the covering before application for material compatibility and colour-fastness.

Turn off any underfloor heating before performing basic cleaning.

When using with machines, the tanks should be regularly cleaned and washed.

Changes or variations in colour of the product do not impact on the quality.

Hazard statements

H318 Causes serious eye damage.

For further safety precautions, please refer to the safety data sheet for Corridor® Power Stripper S 708 at www.buzil.com.

GISBAU code: GG 50

Article number*:

S708-0005

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Date 30.10.2020

BUZIL-WERK Wagner GmbH & Co. KG

Fraunhoferstraße 17 . D-87700 Memmingen T +49 8331 930-6 . F +49 8331 930-880 . E-mail: info@buzil.de . www.buzil.com