

# Corridor® Matt S 737

Silky-matt dispersion



## Area of application

- Ideal for use in healthcare facilities such as hospitals, nursing homes and doctor's offices as well as other areas where disinfectants are used
- Suitable for sports and multi-purpose halls
- For all water-resistant, coatable (including residual moisture) and thoroughly cleaned floor coverings such as PVC and linoleum
- Coatable PUR-modified coverings

## Product properties

- Hard-wearing, silk-matt polymer dispersion
- Very good filling power and good flow properties
- Forms a dirt-repellent and abrasion-resistant care film
- Facilitates maintenance cleaning through higher surface performance
- Fluorine-free
- Silicone-free
- Free of metal salt
- Tested according to FMPA DIN 18032/2 for sports floors
- Optimal alcohol and disinfectant resistance

## Application and dosage

- Shake before use.
- Apply undiluted a thin layer in 2 – 3 layers.
- Consumption: 25 - 35 ml / per m<sup>2</sup> / per order



undiluted

## Note

- Protect from frost.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- Avoid direct sunlight.
- The more thoroughly the stripping and rinsing of open-pore floor coverings such as linoleum are carried out, the better the properties of the coating are supported.
- A single, temporary exposure on the surface without mechanics, to commercially available disinfectants (max. 15 Minutes of continuous stress) is tested and does not cause any damage to the coating surface.
- The product must not be allowed to enter the sewage system, bodies of water or the soil. Product residues must be handed over to authorised disposal companies.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- **Safety:** Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at [www.buzil.com](http://www.buzil.com).
- **Storage:** Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

## Further information

- **Product colour:** white
- **GISBAU code:** GE 10
- **UFI code:** JJU0-K038-C006-775A
- For professional use only.

## Sales units

- S737-0010RA: 1 x 10 l canister



Remark: Some products may not be available in all territories. Please talk to your customer service representative. The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.