

## High gloss floor emulsion

### Description

High-gloss, slip resistant floor emulsion for most types of smooth and water resistant, hard floors. Its technology provides superior traffic resistance against scuffs and dirt. It ensures reduced maintenance costs to improve productivity. It will be ideal in all prestige and heavy traffic areas where ordinary emulsions require a high level of maintenance.

### Key properties

- High-gloss, protective layer
- Hard, durable and wear resistant protection
- Excellent adhesion to most floor types
- Easy to repair

### Benefits

- Enhances the natural appearance of the floor by providing a long lasting high gloss finish
- Superior resistance to scuff marks and dirt, even under heavy traffic
- Suitable for most types of floors such as vinyl, synthetic, linoleum, stone, sealed wood and cork floors
- Spreads evenly for perfect levelling
- Responds to most common maintenance methods
- Suitable for traditional applications with a flat mop, mop and bucket or polish applicators

### Use Instructions

1. Treat only stripped and thoroughly rinsed and completely dry floors. Treat porous and damaged floors with Diversey's floor sealer prior to application.
2. Sparingly pour the product onto the floor and evenly spread it while still wet in overlapping lanes of 1-1.5m. Allow to dry completely before applying additional coats in similar manner. Apply two coats to nonporous, smooth floors. Three coats are usually sufficient for porous floors.
3. **Linoleum:** After the first coat has dried, smooth the linoleum floor with a single disc machine equipped with a blue pad, then damp mop and allow to dry completely before applying additional coats.
4. **Top stripping** and recoating: Use a Diversey floor top stripper to remove one coat of polish and pick up soiled solution with a scrubber drier or wet vacuum cleaner. Allow to dry completely and apply additional coat(s).

### Dosage\*

Ready to use, no dilution required.


Product consumption: min. 20 ml/ m<sup>2</sup> & coat - max. 30 ml/m<sup>2</sup> & coat

\*\*The product doesn't contain intentionally added fluorinated levelling agents (PFAS).

*\*This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*



NO INTENTIONALLY  
ADDED PFAS\*\*



© A.I.S.E



## TASKI® Jontec Shine & Care

### Technical data

Appearance: Milky, white liquid  
pH value (neat):  $\approx 8.7$   
pH value (in use):  $\approx 8.7$   
Relative density (20°C): 1.03 g/cm<sup>3</sup>

*The above data is typical of normal production and should not be taken as a specification.*

### Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; [sds.diversey.com](https://sds.diversey.com). Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

### Product compatibility

Treat only deep cleaned, thoroughly rinsed and completely dry floors. Do not dilute or mix with other substances. Do not use on structured plastic (cushioned vinyl) and unsealed wood or cork. Seek advice for use on profiled/studded rubber floors. Do not use outdoors or in wet zones.

### Available pack sizes

TASKI Jontec Shine & Care is available in 2x5L.

### [www.diversey.com](https://www.diversey.com)

© 2024 Diversey, Inc. All Rights Reserved. 29/07/2024 en (K02339)